
ShoreLandr® | *Go the extra mile*

BOAT TRAILERS



Peace of Mind

ShoreLand'r makes sure you're protected in three different ways: our 5-Year+ Limited Warranty, NMMA Certification and BoatU.S. Protection.

This all adds up to Peace of Mind so you can relax and enjoy every minute of your vacation.

NMMA certified

The "NMMA Certified" decal is your guarantee that every ShoreLand'r is built to meet or exceed the National Marine Manufacturer's Association safety and quality standards. Don't settle for less!

Why ShoreLand'r...

ShoreLand'r goes above and beyond the competition in a number of key areas. It all adds up to a trailer you can depend on year in and year out. Get the most out of every weekend and every summer vacation.

Get a ShoreLand'r and go the extra mile.

Accessorize-ability

Different users have different needs and that's why ShoreLand'r offers a complete line of Genuine ShoreLand'r Accessories. Everything from load guides and spare tires to swing tongues. Whatever it takes to make your trailer fit your lifestyle.

Higher re-sale value

ShoreLand'r has developed a unique, 3-step powder-coating process that creates a deep luster, automotive-style finish. This **Superior Quality Finish** provides long-term protection against fading and chipping so your trailer looks better, longer and holds its value.

Superior Finish

Whether you choose our beautiful powder-coat finish or rugged galvanized, you'll appreciate the extra care we put into making sure your trailer looks good for the long haul.

arctic white | diamond black | rugged galvanized

Better performance at the ramp

All you want to do is get in and get out... and look like a pro doing it. That's precisely why ShoreLand'r trailers have an innovative support System, engineered to take the hassle out of launching and loading..

Roller models feature our **Patented Roller Design.** Specially designed rollers combined with our **Patented Equiload System** make your time at the ramp stress-free. During launching and loading, they self-adjust for maximum hull support and easier centering, even in strong currents and rough winds.

If you prefer bunks, the **Patented Equiload System** uses self-adjusting bunks that pivot to evenly distribute the weight.



Trouble-free LED Lighting System

LED Lights with three separate Fully Grounded, Plug-In Wire Harness enclosed inside the frame & tongue tubes. And our LED lights have the highest quality circuit boards sealed in epoxy and sonic welded lens to withstand a marine environment. All that adds up to a safe, trouble free system that you can count on.



Free BoatU.S. Membership

To protect you in the unlikely event of a breakdown, all ShoreLand'r trailers come with a FREE 90-day BoatU.S. Membership. It features over 26 benefits, including Trailer Assist and Tow and on-the-water towing services.

Five year plus limited warranty

For added peace of mind, our 5-year Plus Limited Warranty includes a 1-Year, Tongue-to-Taillight Warranty. Ask your dealer for details.



Better performance on the road

ShoreLand'r makes the journey as painless as possible with features like smooth rolling **factory-balanced wheels** for better performance and less vibration. Less vibration is a good thing for your boat and its sensitive electronic equipment. In addition to that, the frame is designed to keep the boat riding low for less wind resistance and better gas mileage out on the highway.

Adjustability for the Perfect Fit

The Perfect Fit means better performance both on the road and at the ramp. This is achieved with unique features like the patented, fully-adjustable, and super-stylish **Profile 2000 winch**. The axles are also adjustable to fine-tune tongue weight for perfectly balanced trailering that minimizes stress on your tow vehicle.

Advanced protection for your boat

One of the most important duties of a trailer is to protect your boat when it's out of its element. ShoreLand'r does it with welded **Uni-frame construction** that provides maximum strength and less flex to ensure longer trailer life. Enclosed, Custom Molded Fenders protect your boat from road debris. Protective Pads on all cross-members and axles protect the boat keel if contact is made during loading.

Safety First



You need a trailer that is equipped to protect both your family and your boat in an emergency.

ShoreLand'r doesn't take any chances, featuring **Disc Brakes** to ensure you have the smooth stopping power you need. DOT approved lighting keeps your boat visible at night. Heavy-duty **Double Safety Chains** keep the trailer secured to your tow vehicle. A **Bow Eye Safety Chain** keeps your boat on the trailer if the winch fails. Your safety is our first priority. Period.

Easier Maintenance

Grease-Pack Hubs and **Bearing Protectors** create positive pressure to keep water and contaminants out. This prolongs bearing life and prevent breakdowns, without the hassle of oil-bath systems.



Boating is all about relaxing...

and you can't do that if you're worried about your trailer. That's why all ShoreLand'r trailers, even the smaller models, have the same quality and attention to detail that you'll find in our larger trailers. Combine that with our 5-Year-Plus Limited Warranty and you get one thing – peace of mind.

Rugged Galvanized

Rugged Galvanized for maximum durability, 700 lb. to 8000 lb. capacity models are available with our optional hot-dipped galvanized finish.




SLB7TS


SLR10TM


SLR12TL


SLB14TM



SLR15



SLV15



SLB18LN



SLV22S



SLR22L

Models and specifications are subject to change. Some models are shown with optional equipment.

My Trailer of CHOICE...



"As a cadet at Massachusetts Maritime Academy I have learned a lot about how marine products are engineered and what it takes to be successful in this industry. That's why, when it came time for me to buy a trailer for my own boat, I chose ShoreLand'r. When you look closely at the design and the attention to detail, there is a significant difference. They build trailers the way I would build trailers, and that sold me."

Cadet Thomas S. Long, IV
Massachusetts Maritime Academy
Buzzard's Bay, Mass

SMART BUYER QUESTION

Hit your dealer up with this question and they'll know you're a savvy shopper . . .

"What types of maintenance will I need to do on this trailer?"

Visit www.shorelandr.com for answers to these and hundreds of other trailering questions



1500 LB - 2200 LB

SHORELAND'R BOAT TRAILERS



In today's hustle-bustle world it can be tough...

to find quality family time. When you finally get a chance to break away, you want to spend it relaxing with the kids, not broken down by the side of the highway. That's why a dependable trailer is so important. One with features such as disc brakes, to ensure that all state laws are met, and more importantly, that everyone gets home safely.

? SMART BUYER QUESTION

Hit your dealer up with this question and they'll know you're a savvy shopper . . .

"Do I need load guides on my trailer?"

Visit www.shorelandr.com for answers to these and hundreds of other trailering questions



SLR2314S



SLB2314L



SLR30BSW



SLXR30BLW




SLV30BL



SLR34BLW



SLB40TBLW



SLR46TBS



SLB50TCBL



SLB55TCBBL



SLR68TCBB



SLB80TBBL

Models and specifications are subject to change. Some models are shown with optional equipment.

My Trailer of CHOICE...



"I travel thousands of miles all over the country, filming waterfowl hunting DVD's and TV shows, and pulling a two ton boat blind in the process. I chose ShoreLand'r for its unmatched reliability. At times the film crew and I will be on the road 3 to 4 weeks at a time traveling to different shoots. My ShoreLand'r trailer gives me piece of mind knowing we'll get down the road without a single hiccup."

- Barnie Calef
3 Time World Duck Calling Champion

TESTED & APPROVED

Members of the North American Fishing Club field-tested ShoreLand'r trailers, ranking Design, Quality, Appearance and Ease of Use on a scale of 1 through 10. Our overall score of "9.0" stands as their best trailer rating ever!



4000 LB - 8000 LB

SHORELAND'R BOAT TRAILERS



ShoreLand'r Aluminum Trailers


No other trailer stands up to the rigors and corrosive destruction of saltwater better than ShoreLand'r. Heavy-duty I-beam aluminum frames resist corrosion, with strong, galvanized steel crossmembers and a long list of ShoreLand'r features.

My Trailer of CHOICE...




"When it came time to replace my 20 year old ShoreLand'r, it was a no-brainer. I travel year-round on hunting and fishing projects, so I upgraded to a new aluminum model. The reduced weight helped me out with better gas mileage, and it works great with my new bay boat. By the way... that 20 year old ShoreLand'r – I gave it to a friend and he is still using it today."

- Tom Long, Outdoor Writer






SLIB33B



SLIB40TB



SLIB40TBB



SLIB55TBBL

Models and specifications are subject to change. Some models are shown with optional equipment.



Inboard Trailers

Designed specifically for inboard boats, these models come loaded with unique features, including:

- **EquiLoad® Bunk System**
  Unique pivoting bunks automatically adjust for easier loading and optimum support.
- **Custom Style Fenders**
  This non-corrosive, aluminum diamond plate design has built-in step pads for easy access to your boat.
- **Prop Guard**
  Added protection for the inboard's prop shaft during launching and loading.
- **Post Load Guides**
  For easier loading in windy conditions.



New Pontoon Line Sports More Sizes and New Features

The complete line of ShoreLand'r Pontoon Trailers has been updated with new models to fit today's larger, heavier pontoons. In addition to these new sizes and better fit, these trailers are loaded with great ShoreLand'r features, including:

- **Smooth, Stable Towing**
  heavy-duty tube-steel frame, precision built axles, factory-balanced wheels
- **Long-Term Durability**
  your choice of durable finish - diamond black powder-coat or rugged galvanized, plus impact-resistant Custom Molded Fenders
- **Precise Loading At The Ramp**
  fully carpeted full-length bunks, adjustable winch post, heavy-duty geared winch and dual cushioned deck stops
- **Safe Step-Up Access**
  heavy-duty steps with safety handrail for easy boarding
- **Easy Maintenance**
  dependable grease-pack hubs with bearing protectors, fully-ground wiring with LED side-marker lights
- **Variety Of Accessories**
  tri-toon conversion kits, load guides... and more!




Built To Last

This heavy duty, 3" x 5" tube steel frame is the toughest in the industry. The welded Uniframe construction provides maximum strength and less flex for longer trailer life.

NEW! Trouble-free Lighting System

Sealed taillights with dependable, fully-ground wiring and LED side-marker lights. It all adds up to a trouble-free system you can count on.





User-Friendly

This unique winch post design features dual cushioned deck stops and convenient steps for easy access to your pontoon.

Safety First

Dependable Disc Brakes with corrosion-free rubber brake hoses ensure you have the smooth stopping power you need.

Now standard on all brake models.

Models and specifications are subject to change. Some models are shown with optional equipment.

SMART BUYER QUESTION

Hit your dealer up with this question and they'll know you're a savvy shopper . . .

"Does the law require brakes on this trailer?"

Visit www.shorelandr.com for answers to these and hundreds of other trailering questions



PONTOON SHORELAND'R BOAT TRAILERS

MODELS & SPECIFICATIONS

Models and specifications are subject to change. Recommended carrying capacity is based on the shipping weight of the trailer with standard equipment. Adding optional equipment may decrease the trailer's carrying capacity. Your ShoreLand'r dealer can recommend the specific model that meets your needs.

DECODING SHORELAND'R MODEL NUMBERS

Model numbers provide details about the trailer's capacity and other characteristics.
For example: *SLB40TBLW = a ShoreLand'r Bunk Trailer with 4000 lb. carrying capacity, tandem axles with brakes standard on one axle, and a long-wide frame.*

SL	B	40	T	B	LW
SL = ShoreLand'r	B = Bunk R = Roller V = V-frame bunk XR = Extra roller RB = Roller/Bunk	MAX. CAPACITY (in 100s of lbs.)	T = Tandem/Tri Axle N = Narrow TS = Tongue Short TM = Tongue Medium TL = Tongue Long C = Custom Fender	B = Brakes 1 Axle BB = Brakes 2 Axles	S = Short L = Long SW = Short Wide LW = Long Wide XLW = Ext Long Wide AL = Aluminum

STANDARD MODELS 700 LB. - 1400 LB.

MODEL	TRAILER STYLE	CAPACITY	HULL LENGTH MIN.	HULL LENGTH MAX.	MAX TRN SM TO BOW EYE	MAX OVERALL LENGTH	OVERALL WIDTH	WIDTH BETWEEN FENDERS	TIRE SIZE	BRAKES	LIGHTING
SLB7TS	Bunk	700 lb. (318kg)		12'0" (3.66m)	14'0" (4.27m)	16'8" (5.08m)	59" (1.50m)	46" (1.17m)	4.80X12-B		Submersible
SLB7TL	Bunk	700 lb. (318kg)		16'0" (4.88m)	16'0" (4.88m)	18'8" (5.69m)	59" (1.50m)	46" (1.17m)	4.80X12-B		Submersible
SLB10TS	Bunk	1200 lb. (544kg)	10'11" (3.33m)	12'8" (3.87m)	12'6" (3.86m)	15'6" (4.72m)	59" (1.50m)	46" (1.17m)	4.80X12-B		Submersible
SLR10TS	Roller	1200 lb. (544kg)	10'11" (3.33m)	12'8" (3.87m)	12'6" (3.86m)	15'4" (4.67m)	59" (1.50m)	46" (1.17m)	4.80X12-B		Submersible
SLB10TM	Bunk	1200 lb. (544kg)	12'5" (3.78m)	14'5" (4.39m)	14'2" (4.32m)	17'0" (5.18m)	59" (1.50m)	46" (1.17m)	4.80X12-B		Submersible
SLR10TM	Roller	1200 lb. (544kg)	12'5" (3.78m)	14'5" (4.39m)	14'2" (4.32m)	16'10" (5.13m)	59" (1.50m)	46" (1.17m)	4.80X12-B		Submersible
SLB10TL	Bunk	1200 lb. (544kg)	13'11" (4.24m)	15'11" (4.85m)	15'8" (4.78m)	18'6" (5.64m)	59" (1.50m)	46" (1.17m)	4.80X12-B		Submersible
SLR10TL	Roller	1200 lb. (544kg)	13'11" (4.24m)	15'11" (4.85m)	15'8" (4.78m)	18'4" (5.59m)	59" (1.50m)	46" (1.17m)	4.80X12-B		Submersible
SLB12TS	Roller	1200 lb. (544kg)	11'11" (3.63m)	14'5" (4.39m)	13'11" (4.24m)	17'2" (5.23m)	72" (1.83m)	58" (1.47m)	4.80X12-B	(Opt.)	Submersible
SLB12TM	Bunk	1200 lb. (544kg)	11'11" (3.63m)	14'5" (4.39m)	13'11" (4.24m)	18'8" (5.69m)	72" (1.83m)	58" (1.47m)	4.80X12-B	(Opt.)	Submersible
SLB12TS	Bunk	1200 lb. (544kg)	11'11" (3.63m)	14'5" (4.39m)	13'11" (4.24m)	17'2" (5.23m)	72" (1.83m)	58" (1.47m)	4.80X12-B	(Opt.)	Submersible
SLR12TM	Roller	1200 lb. (544kg)	13'5" (4.09m)	15'11" (4.85m)	15'5" (4.70m)	18'8" (5.69m)	72" (1.83m)	58" (1.47m)	4.80X12-B	(Opt.)	Submersible
SLB12TL	Bunk	1200 lb. (544kg)	14'11" (4.55m)	17'5" (5.31m)	16'11" (5.16m)	20'2" (6.15m)	72" (1.83m)	58" (1.47m)	4.80X12-B	(Opt.)	Submersible
SLR12TL	Roller	1200 lb. (544kg)	14'11" (4.55m)	17'5" (5.31m)	16'11" (5.16m)	20'2" (6.15m)	72" (1.83m)	58" (1.47m)	4.80X12-B	(Opt.)	Submersible
SLR14TS	Roller	1400 lb. (635kg)	11'11" (3.63m)	14'5" (4.39m)	13'11" (4.24m)	17'2" (5.23m)	72" (1.83m)	58" (1.47m)	5.30X12-C	(Opt.)	Submersible
SLB14TM	Bunk	1400 lb. (635kg)	13'5" (4.09m)	15'11" (4.85m)	15'5" (4.70m)	18'8" (5.69m)	72" (1.83m)	58" (1.47m)	5.30X12-C	(Opt.)	Submersible
SLB14TS	Bunk	1400 lb. (635kg)	11'11" (3.63m)	14'5" (4.39m)	13'11" (4.39m)	17'2" (5.23m)	72" (1.83m)	58" (1.47m)	5.30X12-C	(Opt.)	Submersible
SLR14TM	Roller	1400 lb. (635kg)	13'5" (4.09m)	15'11" (4.85m)	15'5" (4.70m)	18'8" (5.69m)	72" (1.83m)	58" (1.47m)	5.30X12-C	(Opt.)	Submersible
SLB14TL	Bunk	1400 lb. (635kg)	14'11" (4.55m)	17'5" (5.31m)	16'11" (5.16m)	20'2" (6.15m)	72" (1.83m)	58" (1.47m)	5.30X12-C	(Opt.)	Submersible
SLR14TL	Roller	1400 lb. (635kg)	14'11" (4.55m)	17'5" (5.31m)	16'11" (5.16m)	20'2" (6.15m)	72" (1.83m)	58" (1.47m)	5.30X12-C	(Opt.)	Submersible

STANDARD MODELS 1500 LB. - 2200 LB.

MODEL	TRAILER STYLE	CAPACITY	HULL LENGTH MIN.	HULL LENGTH MAX.	MAX TRN SM TO BOW EYE	MAX OVERALL LENGTH	OVERALL WIDTH	WIDTH BETWEEN FENDERS	TIRE SIZE	BRAKES	LIGHTING
SLR15	Roller	1500 lb. (680kg)	14' (4.27m)	16' (4.88m)	15'8" (4.78m)	18'6" (5.64m)	79.5" (2.02m)	66" (1.68m)	5.30X12-C	8.5" Drum (Opt.)	Submersible
SLV15	V-Bunk	1500 lb. (680kg)	14' (4.27m)	15'6" (4.72m)	15' (4.57m)	17'10" (5.44m)	79.5" (2.02m)	66" (1.68m)	5.30X12-C	8.5" Drum (Opt.)	Submersible
SLB18LN	Bunk	1800 lb. (816kg)	16' (4.88m)	18' (5.49m)	16'9" (5.11m)	19'11" (6.07m)	84" (2.13m)	68" (1.73m)	ST175/80R13-C	10" Disc (Opt.)	Sealed LED
SLR18LN	Roller	1800 lb. (816kg)	16' (4.88m)	18' (5.49m)	16'9" (5.11m)	19'11" (6.07m)	84" (2.13m)	68" (1.73m)	ST175/80R13-C	10" Disc (Opt.)	Sealed LED
SLV18LN	V-Bunk	1800 lb. (816kg)	16' (4.88m)	17'4" (5.28m)	16'1" (4.90m)	19'3" (5.87m)	84" (2.13m)	68" (1.73m)	ST175/80R13-C	10" Disc (Opt.)	Sealed LED



STANDARD MODELS 1500 LB. - 2200 LB. CONTINUED

MODEL	TRAILER STYLE	CAPACITY	HULL LENGTH MIN.	HULL LENGTH MAX.	MAX TRN SM TO BOW EYE	MAX OVERALL LENGTH	OVERALL WIDTH	WIDTH BETWEEN FENDERS	TIRE SIZE	BRAKES	LIGHTING
SLR22S	Roller	2200 lb. (998kg)	14' (4.27m)	16' (4.88m)	15'4" (4.67m)	18'5" (5.61m)	89" (2.26m)	74" (1.88m)	ST185/80R13-C	10" Disc (Opt.)	Sealed LED
SLV22S	V-Bunk	2200 lb. (998kg)	14' (4.27m)	15' (4.57m)	14'8" (4.47m)	17'9" (5.41m)	89" (2.26m)	74" (1.88m)	ST185/80R13-C	10" Disc (Opt.)	Sealed LED
SLB22L	Bunk	2200 lb. (998kg)	16' (4.88m)	18' (5.49m)	16'9" (5.11m)	19'11" (6.07m)	89" (2.26m)	74" (1.88m)	ST185/80R13-C	10" Disc (Opt.)	Sealed LED
SLR22L	Roller	2200 lb. (998kg)	16' (4.88m)	18' (5.49m)	16'9" (5.11m)	19'11" (6.07m)	89" (2.26m)	74" (1.88m)	ST185/80R13-C	10" Disc (Opt.)	Sealed LED
SLV22L	V-Bunk	2200 lb. (998kg)	16' (4.88m)	17'4" (5.28m)	16'1" (4.90m)	19'3" (5.87m)	89" (2.26m)	74" (1.88m)	ST185/80R13-C	10" Disc (Opt.)	Sealed LED
SLB22LW	Bunk	2200 lb. (998kg)	16' (4.88m)	18' (5.49m)	16'9" (5.11m)	19'11" (6.07m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc (Opt.)	Sealed LED
SLR22LW	Roller	2200 lb. (998kg)	16' (4.88m)	18' (5.49m)	16'9" (5.11m)	19'11" (6.07m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc (Opt.)	Sealed LED
SLV22LW	V-Bunk	2200 lb. (998kg)	16' (4.88m)	17'4" (5.28m)	16'1" (4.90m)	19'3" (5.87m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc (Opt.)	Sealed LED

STANDARD MODELS 2300 LB. - 3400 LB.

MODEL	TRAILER STYLE	CAPACITY	HULL LENGTH MIN.	HULL LENGTH MAX.	MAX TRN SM TO BOW EYE	MAX OVERALL LENGTH	OVERALL WIDTH	WIDTH BETWEEN FENDERS	TIRE SIZE	BRAKES	LIGHTING
SLB2314S	Bunk	2300 lb. (1043kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	20'1" (6.12m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C		Sealed LED
SLR2314S	Roller	2300 lb. (1043kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	20'1" (6.12m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C		Sealed LED
SLRB2314S	Roller-Bunk	2300 lb. (1043kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	20'1" (6.12m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C		Sealed LED
SLV2314S	V-Bunk	2300 lb. (1043kg)	17' (5.18m)	18' (5.49m)	16'4" (4.98m)	19'1" (5.82m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C		Sealed LED
SLXR2314S	XR Roller	2300 lb. (1043kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	20'1" (6.12m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C		Sealed LED
SLB2314L	Bunk	2300 lb. (1043kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	21'1" (6.43m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C		Sealed LED
SLR2314L	Roller	2300 lb. (1043kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	21'1" (6.43m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C		Sealed LED
SLRB2314L	Roller-Bunk	2300 lb. (1043kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	21'1" (6.43m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C		Sealed LED
SLV2314L	V-Bunk	2300 lb. (1043kg)	18' (5.49m)	19' (5.79m)	17'4" (5.28m)	20'1" (6.12m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C		Sealed LED
SLXR2314L	XR Roller	2300 lb. (1043kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	21'1" (6.43m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C		Sealed LED
SLB2314SW	Bunk	2300 lb. (1043kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	20'1" (6.12m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C		Sealed LED
SLR2314SW	Roller	2300 lb. (1043kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	20'1" (6.12m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C		Sealed LED
SLRB2314SW	Roller-Bunk	2300 lb. (1043kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	20'1" (6.12m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C		Sealed LED
SLV2314SW	V-Bunk	2300 lb. (1043kg)	17' (5.18m)	18' (5.79m)	16'4" (4.98m)	19'1" (5.82m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C		Sealed LED
SLXR2314SW	XR Roller	2300 lb. (1043kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	20'1" (6.12m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C		Sealed LED
SLB2314LW	Bunk	2300 lb. (1043kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C		Sealed LED





STANDARD MODELS 2300 LB. - 3400 LB. CONTINUED

MODEL	TRAILER STYLE	CAPACITY	HULL LENGTH MIN.	HULL LENGTH MAX.	MAX TRIM SW TO BOW EYE	MAX OVERALL LENGTH	OVERALL WIDTH	WIDTH BETWEEN FENDERS	TIRE SIZE	BRAKES	LIGHTING
SLR2314LW	Roller	2300 lb. (1043kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	21'1" (6.43m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C		Sealed LED
SLRB2314LW	Roller-Bunk	2300 lb. (1043kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	21'1" (6.43m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C		Sealed LED
SLV2314LW	V-Bunk	2300 lb. (1043kg)	18' (5.49m)	19' (5.79m)	17'4" (5.28m)	20'1" (6.12m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C		Sealed LED
SLXR2314LW	XR Roller	2300 lb. (1043kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	21'1" (6.43m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C		Sealed LED
SLB30BS	Bunk	3000 lb. (1361kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	21'1" (6.43m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C	10" Disc	Sealed LED
SLR30BS	Roller	3000 lb. (1361kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	21'1" (6.43m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C	10" Disc	Sealed LED
SLRB30BS	Roller-Bunk	3000 lb. (1361kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	21'1" (6.43m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C	10" Disc	Sealed LED
SLV30BS	V-Bunk	3000 lb. (1361kg)	17' (5.18m)	18' (5.49m)	16'4" (4.98m)	20'1" (6.12m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C	10" Disc	Sealed LED
SLXR30BS	XR Roller	3000 lb. (1361kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	21'1" (6.43m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C	10" Disc	Sealed LED
SLB30BL	Bunk	3000 lb. (1361kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C	10" Disc	Sealed LED
SLR30BL	Roller	3000 lb. (1361kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C	10" Disc	Sealed LED
SLRB30BL	Roller-Bunk	3000 lb. (1361kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C	10" Disc	Sealed LED
SLV30BL	V-Bunk	3000 lb. (1361kg)	18' (5.49m)	19' (5.79m)	17'4" (5.28m)	21'1" (6.43m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C	10" Disc	Sealed LED
SLXR30BL	XR Roller	3000 lb. (1361kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	95.5" (2.43m)	78.5" (1.99m)	ST215/75R14-C	10" Disc	Sealed LED
SLB30BSW	Bunk	3000 lb. (1361kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	21'1" (6.43m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLR30BSW	Roller	3000 lb. (1361kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	21'1" (6.43m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	1Sealed LED
SLRB30BSW	Roller-Bunk	3000 lb. (1361kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	21'1" (6.43m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLV30BSW	V-Bunk	3000 lb. (1361kg)	17' (5.18m)	18' (5.49m)	16'4" (4.98m)	20'1" (6.12m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLXR30BSW	XR Roller	3000 lb. (1361kg)	17' (5.18m)	19' (5.79m)	17'4" (5.28m)	21'1" (6.43m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLB30BLW	Bunk	3000 lb. (1361kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLR30BLW	Roller	3000 lb. (1361kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLRB30BLW	Roller-Bunk	3000 lb. (1361kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLV30BLW	V-Bunk	3000 lb. (1361kg)	18' (5.49m)	19' (5.79m)	17'4" (5.28m)	21'1" (6.43m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLXR30BLW	XR Roller	3000 lb. (1361kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLB30BXLW	Bunk	3000 lb. (1361kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLR30BXLW	Roller	3000 lb. (1361kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLRB30BXLW	Roller-Bunk	3000 lb. (1361kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLXR30BXLW	XR Roller	3000 lb. (1361kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED

STANDARD MODELS 2300 LB. - 3400 LB. CONTINUED

MODEL	TRAILER STYLE	CAPACITY	HULL LENGTH MIN.	HULL LENGTH MAX.	MAX TRIM SW TO BOW EYE	MAX OVERALL LENGTH	OVERALL WIDTH	WIDTH BETWEEN FENDERS	TIRE SIZE	BRAKES	LIGHTING
SLB34BLW	Bunk	3400 lb. (1542kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST205/75R15-D	12" Disc	Sealed LED
SLR34BLW	Roller	3400 lb. (1542kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST205/75R15-D	12" Disc	Sealed LED
SLRB34BLW	Roller-Bunk	3400 lb. (1542kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST205/75R15-D	12" Disc	Sealed LED
SLXR34BLW	XR Roller	3400 lb. (1542kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST205/75R15-D	12" Disc	Sealed LED
SLB34BXLW	Bunk	3400 lb. (1542kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST205/75R15-D	12" Disc	Sealed LED
SLR34BXLW	Roller	3400 lb. (1542kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST205/75R15-D	12" Disc	Sealed LED
SLRB34BXLW	Roller-Bunk	3400 lb. (1542kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST205/75R15-D	12" Disc	Sealed LED
SLXR34BXLW	XR Roller	3500 lb. (1588kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST205/75R15-D	12" Disc	Sealed LED

STANDARD MODELS 4000 LB. - 8000 LB.

MODEL	TRAILER STYLE	CAPACITY	HULL LENGTH MIN.	HULL LENGTH MAX.	MAX TRIM SW TO BOW EYE	MAX OVERALL LENGTH	OVERALL WIDTH	WIDTH BETWEEN FENDERS	TIRE SIZE	BRAKES	LIGHTING
SLB40TBLW	Bunk	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 1 Axle	Sealed LED
SLR40TBLW	Roller	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 1 Axle	Sealed LED
SLRB40TBLW	Roller-Bunk	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 1 Axle	Sealed LED
SLXR40TBLW	XR Roller	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 1 Axle	Sealed LED
SLB40TBBLW	Bunk	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 2 Axles	Sealed LED
SLR40TBBLW	Roller	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 2 Axles	Sealed LED
SLRB40TBBLW	Roller-Bunk	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	Disc 2 Axles	Sealed LED
SLXR40TBBLW	XR Roller	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 2 Axles	Sealed LED
SLB40TBXLW	Bunk	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 1 Axle	Sealed LED
SLR40TBXLW	Roller	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 1 Axle	Sealed LED
SLRB40TBXLW	Roller-Bunk	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 1 Axle	Sealed LED
SLXR40TBXLW	XR Roller	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 1 Axle	Sealed LED
SLB40TBBXLW	Bunk	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 2 Axles	Sealed LED
SLR40TBBXLW	Roller	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 2 Axles	Sealed LED
SLRB40TBBXLW	Roller-Bunk	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 2 Axles	Sealed LED
SLXR40TBBXLW	XR Roller	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 2 Axles	Sealed LED
SLB40TCBLW	Bunk	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED
SLR40TCBLW	Roller	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED





STANDARD MODELS 4000 LB. - 8000 LB. CONTINUED

MODEL	TRAILER STYLE	CAPACITY	HULL LENGTH MIN.	HULL LENGTH MAX.	MAX TRNSM TO BOW EYE	MAX OVERALL LENGTH	OVERALL WIDTH	WIDTH BETWEEN FENDERS	TIRE SIZE	BRAKES	LIGHTING
SLRB40TCBLW	Roller-Bunk	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED
SLXR40TCBLW	XR Roller	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED
SLB40TCBBLW	Bunk	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLR40TCBBLW	Roller	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLRB40TCBBLW	Roller-Bunk	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLXR40TCBBLW	XR Roller	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLB40TCBXLW	Bunk	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED
SLR40TCBXLW	Roller	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED
SLRB40TCBXLW	Roller-Bunk	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED
SLXR40TCBXLW	XR Roller	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED
SLB40TCBBXLW	Bunk	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLR40TCBBXLW	Roller	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLRB40TABBXW	Roller-Bunk	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLXR40TABBXW	XR Roller	4000 lb. (1814kg)	19' (5.79m)	20' (6.10m)	18'4" (5.59m)	22'1" (6.73m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLB46TBS	Bunk	4600 lb. (2087kg)	19' (5.79m)	23' (7.01m)	21'8" (6.60m)	24'8" (7.52m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 1 Axle	Sealed LED
SLR46TBS	Roller	4600 lb. (2087kg)	19' (5.79m)	23' (7.01m)	21'8" (6.60m)	24'8" (7.52m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 1 Axle	Sealed LED
SLRB46TBS	Roller-Bunk	4600 lb. (2087kg)	19' (5.79m)	23' (7.01m)	21'8" (6.60m)	24'11" (7.59m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 1 Axle	Sealed LED
SLB46TBBS	Bunk	4600 lb. (2087kg)	19' (5.79m)	23' (7.01m)	21'8" (6.60m)	24'8" (7.52m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 2 Axles	Sealed LED
SLR46TBBS	Roller	4600 lb. (2087kg)	19' (5.79m)	23' (7.01m)	21'8" (6.60m)	24'8" (7.52m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 2 Axles	Sealed LED
SLRB46TBBS	Roller-Bunk	4600 lb. (2087kg)	19' (5.79m)	23' (7.01m)	21'8" (6.60m)	24'8" (7.52m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 2 Axles	Sealed LED
SLB46TBL	Bunk	4600 lb. (2087kg)	20'6" (6.25m)	24'6" (7.47m)	23'2" (7.06m)	26'2" (7.98m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 1 Axle	Sealed LED
SLR46TBL	Roller	4600 lb. (2087kg)	20'6" (6.25m)	24'6" (7.47m)	23'2" (7.06m)	26'2" (7.98m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 1 Axle	Sealed LED
SLRB46TBL	Roller-Bunk	4600 lb. (2087kg)	20'11" (6.38m)	24'11" (7.59m)	23'7" (7.19m)	26'7" (8.10m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 1 Axle	Sealed LED
SLB46TBBL	Bunk	4600 lb. (2087kg)	20'6" (6.25m)	24'6" (7.47m)	23'2" (7.06m)	26'2" (7.98m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 2 Axles	Sealed LED
SLRB46TBL	Roller-Bunk	4600 lb. (2087kg)	20'11" (6.38m)	24'11" (7.59m)	23'7" (7.19m)	26'7" (8.10m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 1 Axle	Sealed LED
SLRB46TBBL	Roller	4600 lb. (2087kg)	20'6" (6.25m)	24'6" (7.47m)	23'2" (7.06m)	26'2" (7.98m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 2 Axles	Sealed LED
SLB50TCBS	Bunk	5000 lb. (2267kg)	19' (5.79m)	23' (7.01m)	21'8" (6.60m)	24'8" (7.52m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED
SLB50TCBL	Bunk	5000 lb. (2267kg)	20'6" (6.25m)	24'6" (7.47m)	23'2" (7.06m)	26'2" (7.98m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED
SLR50TCBS	Roller	5000 lb. (2267kg)	19' (5.79m)	23' (7.01m)	21'8" (6.60m)	24'8" (7.52m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED
SLR50TCBL	Roller	5000 lb. (2267kg)	20'6" (6.25m)	24'6" (7.47m)	23'2" (7.06m)	26'2" (7.98m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED

STANDARD MODELS 4000 LB. - 8000 LB. CONTINUED

MODEL	TRAILER STYLE	CAPACITY	HULL LENGTH MIN.	HULL LENGTH MAX.	MAX TRNSM TO BOW EYE	MAX OVERALL LENGTH	OVERALL WIDTH	WIDTH BETWEEN FENDERS	TIRE SIZE	BRAKES	LIGHTING
SLRB50TCBS	Roller-Bunk	5000 lb. (2267kg)	19' (5.79m)	23' (7.01m)	21'8" (6.60m)	24'8" (7.52m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED
SLRB50TCBL	Roller-Bunk	5000 lb. (2267kg)	20'11" (6.38m)	24'11" (7.59m)	23'7" (7.19m)	26'7" (8.10m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 1 Axle	Sealed LED
SLB55TCBBL	Bunk	5500 lb. (2495kg)	20'6" (6.25m)	24' (7.32m)	22'8" (6.91m)	26'8" (8.13m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLR55TCBBL	Roller	5500 lb. (2495kg)	20'6" (6.25m)	24' (7.32m)	22'8" (6.91m)	26'8" (8.13m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLRB55TCBBL	Roller-Bunk	5500 lb. (2495kg)	20'6" (6.25m)	24' (7.32m)	22'8" (6.91m)	26'8" (8.13m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLB58TCBB	Bunk	5800 lb. (2631kg)	22' (6.71m)	25' (7.62m)	23'5" (7.14m)	28'2" (8.59m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLR58TCBB	Roller	5800 lb. (2631kg)	22' (6.71m)	25' (7.62m)	23'5" (7.14m)	28'2" (8.59m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLB68TCBB	Bunk	6800 lb. (3084kg)	22' (6.71m)	25' (7.62m)	23'5" (7.14m)	28'2" (8.59m)	101.5" (2.58m)	84.5" (2.15m)	ST205/75R15-D	12" Disc 2 Axles	Sealed LED
SLR68TCBB	Roller	6800 lb. (3084kg)	22' (6.71m)	25' (7.62m)	23'5" (7.14m)	28'2" (8.59m)	101.5" (2.58m)	84.5" (2.15m)	ST205/75R15-D	12" Disc 2 Axles	Sealed LED
SLB80TBBL	Bunk	8000 lb. (3629kg)	24' (7.32m)	27' (8.23m)	24'7" (7.49m)	29'4" (8.94m)	101.5" (2.58m)	81.5" (2.15m)	ST225/75R15-D	12" Disc 2 Axles	Sealed LED
SLR80TBBL	Roller	8000 lb. (3629kg)	24' (7.32m)	27' (8.23m)	24'7" (7.49m)	29'4" (8.94m)	101.5" (2.58m)	81.5" (2.15m)	ST225/75R15-D	12" Disc 2 Axles	Sealed LED

ALUMINUM MODELS

MODEL	TRAILER STYLE	CAPACITY	HULL LENGTH MIN.	HULL LENGTH MAX.	MAX TRNSM TO BOW EYE	MAX OVERALL LENGTH	OVERALL WIDTH	WIDTH BETWEEN FENDERS	TIRE SIZE	BRAKES	LIGHTING
SLB30BAL	Bunk	3000 lb. (1361kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	21'10" (6.65m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLB40TBAL	Bunk	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	21'10" (6.65m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 1 Axle	Sealed LED
SLB40TBBAL	Bunk	4000 lb. (1814kg)	18' (5.49m)	20' (6.10m)	18'4" (5.59m)	21'10" (6.65m)	99.5" (2.53m)	84.5" (2.15m)	ST175/80R13-C	10" Disc 2 Axles	Sealed LED
SLB46TBAL	Bunk	4600 lb. (2087g)	20' (6.10m)	23' (7.01m)	21'8" (6.60m)	23'8" (7.21m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 1 Axle	Sealed LED
SLB46TBBAL	Bunk	4600 lb. (2087g)	20' (6.10m)	23' (7.01m)	21'8" (6.60m)	23'8" (7.21m)	99.5" (2.53m)	84.5" (2.15m)	ST185/80R13-C	10" Disc 2 Axles	Sealed LED
SLB60TAL	Bunk	6000 lb. (2722g)	22' (6.71m)	25' (7.62m)	22'8" (6.91m)	27'6" (8.38m)	101.5" (2.58m)	84.5" (2.15m)	ST215/75R14-C	10" Disc 2 Axles	Sealed LED
SLB70TAL	Bunk	7000 lb. (3175g)	22' (6.71m)	25' (7.62m)	22'8" (6.91m)	27'6" (8.38m)	101.5" (2.58m)	84.5" (2.15m)	ST205/75R15-D	12" Disc 2 Axles	Sealed LED
SLB82TAL	Bunk	8200 lb. (3719g)	24' (7.32m)	27' (8.23m)	23'10" (7.26m)	29'10" (9.09m)	101.5" (2.58m)	83.5" (2.12m)	ST225/75R15-D	12" Disc 2 Axles	Sealed LED
SLB95TAL	Bunk	9500 lb. (4309g)	28' (8.53m)	31' (9.45m)	26'9" (8.15m)	33'0" (10.06m)	101.5" (2.58m)	83" (2.11m)	LT235/85R16-E	12" Disc 2 Axles	Sealed LED
SLR95TAL	Roller	9500 lb. (4309g)	28' (8.53m)	31' (9.45m)	26'9" (8.15m)	33'0" (10.06m)	101.5" (2.58m)	83" (2.11m)	LT235/85R16-E	12" Disc 2 Axles	Sealed LED
SLB150TAL	Bunk	15000 lb. (6804g)	32' (9.75m)	36' (10.97m)	31'10" (9.70m)	35'11" (10.95m)	101.5" (2.58m)	81" (2.06m)	LT235/85R16-E	12" Disc 3 Axles	Sealed LED
SLR150TAL	Roller	15000 lb. (6804g)	32' (9.75m)	36' (10.97m)	31'10" (9.70m)	35'11" (10.95m)	101.5" (2.58m)	81" (2.06m)	LT235/85R16-E	12" Disc 3 Axles	Sealed LED
SLKB150TAL	Bunk	15000 lb. (6804g)	32' (9.75m)	36' (10.97m)	31'10" (9.70m)	35'11" (10.95m)	101.5" (2.58m)	81" (2.06m)	LT235/85R16-E	12" Disc 3 Axles	Sealed LED





PONTOON

MODEL	TRAILER STYLE	CAPACITY	HULL LENGTH MIN.	HULL LENGTH MAX.	MAX OVERALL LENGTH	OVERALL WIDTH	TIRE SIZE	BRAKES	LIGHTING
PT1415	Pontoon	1500 lb. (680kg)	8' (2.44m)	14' (4.27m)	17'5" (5.31m)	80.25" (2.04m)	5.30x12-C	N/A	Submersible
PT1420	Pontoon	2000 lb. (907kg)	10' (3.05m)	14' (4.27m)	18'6" (5.64m)	102" (2.59m)	20.5x8.0x10-E	8" Disc (Opt.)	Submersible
PT1720	Pontoon	2000 lb. (907kg)	14' (4.27m)	17' (5.18m)	21'6" (6.55m)	102" (2.59m)	20.5x8.0x10-E	8" Disc (Opt.)	Submersible
PT1922	Pontoon	2200 lb. (998kg)	16' (4.88m)	19' (5.79m)	23'1" (7.04m)	96.5" (2.45m)	20.5x8.0x10-E	8" Disc (Opt.)	Submersible
PT1922B	Pontoon	2200 lb. (998kg)	16' (4.88m)	19' (5.79m)	24'1" (7.34m)	96.5" (2.45m)	20.5x8.0x10-E	8" Disc Standard	Submersible
PT1922A	Pontoon	2200 lb. (998kg)	16' (4.88m)	19' (5.79m)	23'1" (7.04m)	93.5" (2.37m)	ST185/80R13-C	10" Disc (Opt.)	Submersible
PT1925AB	Pontoon	2500 lb. (1134kg)	16' (4.88m)	19' (5.79m)	24'1" (7.34m)	93.5" (2.37m)	ST185/80D13-D	10" Disc Standard	Submersible
PT2122	Pontoon	2200 lb. (998kg)	17' (5.18m)	21' (6.40m)	24'9" (7.54m)	96.5" (2.45m)	20.5x8.0x10-E	8" Disc (Opt.)	Submersible
PT2122B	Pontoon	2200 lb. (998kg)	17' (5.18m)	21' (6.40m)	25'9" (7.85m)	96.5" (2.45m)	20.5x8.0x10-E	8" Disc Standard	Submersible
PT2122A	Pontoon	2200 lb. (998kg)	17' (5.18m)	21' (6.40m)	24'9" (7.54m)	93.5" (2.37m)	ST185/80R13-C	10" Disc (Opt.)	Submersible
PT2125AB	Pontoon	2500 lb. (1134kg)	18' (5.49m)	21' (6.40m)	25'9" (7.85m)	93.5" (2.37m)	ST185/80D13-D	10" Disc Standard	Submersible
PT2127AB	Pontoon	2700 lb. (1225kg)	18' (5.49m)	21' (6.40m)	25'9" (7.85m)	93.5" (2.37m)	ST215/75R14-C	10" Disc Standard	Submersible
PT2147TB	Pontoon	4700 lb. (2132kg)	17' (5.18m)	21' (6.40m)	25'9" (7.85m)	96.5" (2.45m)	71"20.5x8.0x10-E	8" Disc Standard 1 Axle	Submersible
PT2147TBB	Pontoon	4700 lb. (2132kg)	17' (5.18m)	21' (6.40m)	25'9" (7.85m)	96.5" (2.45m)	20.5x8.0x10-E	8" Disc Standard 2 Axles	Submersible
PT2147TAB	Pontoon	4700 lb. (2132kg)	17' (5.18m)	21' (6.40m)	25'9" (7.85m)	93.5" (2.37m)	ST185/80R13-C	10" Disc Standard 1 Axle	Submersible
PT2147TABB	Pontoon	4700 lb. (2132kg)	17' (5.18m)	21' (6.40m)	25'9" (7.85m)	93.5" (2.37m)	ST185/80R13-C	10" Disc Standard 2 Axles	Submersible
PT2321A	Pontoon	2100 lb. (953kg)	20' (6.10m)	23' (7.01m)	28'8" (8.74m)	93.5" (2.37m)	ST185/80D13-D	10" Disc (Opt.)	Submersible
PT2325AB	Pontoon	2500 lb. (1134kg)	20' (6.10m)	23' (7.01m)	27'11" (8.51m)	93.5" (2.37m)	ST185/80D13-D	10" Disc Standard	Submersible
PT2327AB	Pontoon	2700 lb. (1225kg)	20' (6.10m)	23' (7.01m)	27'11" (8.51m)	93.5" (2.37m)	ST215/75R14-C	10" Disc Standard	Submersible
PT2347TB	Pontoon	4700 lb. (2132kg)	20' (6.10m)	23' (7.01m)	27'11" (8.51m)	96.5" (2.45m)	20.5x8.0x10-E	8" Disc Standard 1 Axle	Submersible
PT2347TBB	Pontoon	4700 lb. (2132kg)	20' (6.10m)	23' (7.01m)	27'11" (8.51m)	96.5" (2.45m)	20.5x8.0x10-E	8" Disc Standard 2 Axles	Submersible
PT2347TAB	Pontoon	4700 lb. (2132kg)	20' (6.10m)	23' (7.01m)	27'11" (8.51m)	93.5" (2.37m)	ST185/80R13-C	10" Disc Standard 1 Axle	Submersible
PT2347TABB	Pontoon	4700 lb. (2132kg)	20' (6.10m)	23' (7.01m)	27'11" (8.51m)	93.5" (2.37m)	ST185/80R13-C	10" Disc Standard 2 Axles	Submersible
PT2547TB	Pontoon	4700 lb. (2132kg)	22' (6.71m)	25' (7.62m)	30'11" (9.42m)	96.5" (2.45m)	20.5x8.0x10-E	8" Disc Standard 1 Axle	Submersible
PT2547TBB	Pontoon	4700 lb. (2132kg)	22' (6.71m)	25' (7.62m)	30'11" (9.42m)	96.5" (2.45m)	20.5x8.0x10-E	8" Disc Standard 2 Axles	Submersible
PT2550TAB	Pontoon	5000 lb. (2268kg)	22' (6.71m)	25' (7.62m)	30'11" (9.42m)	93.5" (2.37m)	ST185/80D13-D	10" Disc Standard 1 Axle	Submersible
PT2555TABB	Pontoon	5500 lb. (2495kg)	22' (6.71m)	25' (7.62m)	30'11" (9.42m)	93.5" (2.37m)	ST185/80D13-D	10" Disc Standard 2 Axles	Submersible
PT2947TB	Pontoon	4700 lb. (2132kg)	26' (7.92m)	29' (8.84m)	32' (9.75m)	96.5" (2.45m)	20.5x8.0x10-E	8" Disc Standard 1 Axle	Submersible
PT2947TBB	Pontoon	4700 lb. (2132kg)	26' (7.92m)	29' (8.84m)	32' (9.75m)	96.5" (2.45m)	ST185/80R13-C	8" Disc Standard 1 Axle	Submersible
PT2950TAB	Pontoon	5000 lb. (2268kg)	26' (7.92m)	29' (8.84m)	32' (9.75m)	93.5" (2.37m)	ST185/80D13-D	10" Disc Standard 1 Axle	Submersible
PT2955TABB	Pontoon	5500 lb. (2495kg)	26' (7.92m)	29' (8.84m)	32' (9.75m)	93.5" (2.37m)	ST185/80D13-D	10" Disc Standard 2 Axles	Submersible

INBOARD

MODEL	TRAILER STYLE	CAPACITY	HULL LENGTH MIN.	HULL LENGTH MAX.	MAX TRNSM TO BOW EYE	OVERALL WIDTH	OVERALL LENGTH	BETWEEN FENDERS	TIRE SIZE	BRAKES	LIGHTING
SLIB33TB	Inboard	3300 lb. (1497kg)	20' (6.10m)	21' (6.40m)	19'4" (5.89m)	95.5" (2.43m)	24' (7.32m)	78.5" (1.99m)	ST205/75R15-D	12" Disc	Sealed LED
SLIB40TB	Inboard	4000 lb. (1814kg)	20' (6.10m)	21' (6.40m)	19'4" (5.89m)	93.5" (2.37m)	24' (7.32m)	78.5" (1.99m)	ST215/75R14-C	10" Disc	Sealed LED
SLIB40TBB	Inboard	4000 lb. (1814kg)	20' (6.10m)	21' (6.40m)	19'4" (5.89m)	95.5" (2.43m)	24' (7.32m)	78.5" (1.99m)	ST215/75R14-C	10" Disc	Sealed LED
SLIB2E55TBBL	Inboard	5500 lb. (2495kg)	21' (6.40m)	24' (7.32m)	22'1" (6.73m)	102" (2.59m)	25'10" (7.87m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED
SLIB55TBBL	Inboard	5500 lb. (2495kg)	21' (6.40m)	24' (7.32m)	22'1" (6.73m)	102" (2.59m)	25'10" (7.87m)	84.5" (2.15m)	ST215/75R14-C	10" Disc	Sealed LED

Superior Finish

Whether you choose our beautiful powder-coat finish or rugged galvanized, you'll appreciate the extra care we put into making sure your trailer looks good for the long haul.

Powder-coated paint

Our special powder coating system provides more uniform coverage for a deep luster finish. Available in your choice of colors:

arctic white
available on
2300 lb. to 8000 lb. models

diamond black
available on
700 lb. to 8000 lb. models

rugged galvanized
available on
700 lb. to 8000 lb. models

Visit **www.shorelandr.com** *for the latest updates!*

SHORELAND'R SPECIALTY TRAILERS

PWC & POWERSPORTS





PWC & Powersports Trailers

ShoreLand'r also offers a complete line of PWC and Powersports trailers for all kinds of tools and toys, including:

- *Personal Watercraft*
- *ATVs*
- *UTVs*
- *Motorcycles*
- *Golf Carts*
- *Lawn Mowers*
- *.... and much, much more!*

No matter what you are hauling, there is a dependable ShoreLand'r trailer that can get the job done.

Visit shorelandr.com to see the whole line.



PWCD2213



PS6X12

AUTHORIZED DEALER

ShoreLandr® | Go the extra mile

Midwest Industries, Inc.
Ida Grove, Iowa 51445
800.859.3028
shorelandr.com

0004021 B1112199
Revised 12/11