

# SPECIFICATIONS:

MODEL	# OF VEHICLE(S)	INSIDE BED WIDTH	BED LENGTH	LENGTH INCL.V-NOSE	OVERALL LENGTH	GVWR	TRAILER WEIGHT	CARRYING CAPACITY	# OF AXLES	BALL SIZE	HITCH HEIGHT *	STD. TIRE	TIRE UPGRADE
XT 7' WIDE		(IN.)	(FT.)	(FT.)	(FT.)					(IN.)	NOTE: TOP OF BALL		
<b>XT-127</b>	2	80.5	12	17	20.5	5000	1350	3650	2	2	18	ST205/75 R14C	ST205/75 R14C ALUM RIMS
<b>XT-147</b>	2	80.5	14	19	22.5	5000	1450	3550	2	2	18	ST205/75 R14C	ST205/75 R14C ALUM RIMS
<b>XT-187</b>	2-3	80.5	18	23	26.5	6000	1650	4350	2	2	18	ST205/75 R14C	ST205/75 R14C ALUM RIMS
<b>XT-227</b>	4	80.5	22	27	30.5	6000	2100	3900	2	2	18	ST205/75 R14C	ST205/75 R14C ALUM RIMS
<b>XT-247</b>	4	80.5	24	29	32.5	6000	2325	3675	2	2	18	ST205/75 R14C	ST205/75 R14C ALUM RIMS
<b>XT 8' WIDE</b>													
<b>XT-128-1</b>	2	98	12	17	20	2995	1190	1805	1	2	25	175/80 R13D	165/75 R13D ALUM RIMS
<b>XT-128-2</b>	2	98	12	17	20	5000	1400	3600	2	2	25	175/80 R13D	165/75 R13D ALUM RIMS
<b>XT-168</b>	2-3	98	16	21	24	5000	1700	3300	2	2	25	175/80 R13D	165/75 R13D ALUM RIMS
<b>XT-208</b>	3-4	98	20	25	28	6000	2150	3850	2	2	25	175/80 R13D	165/75 R13D ALUM RIMS
<b>XT-228</b>	4	98	22	27	30	6000	2275	3725	2	2	25	175/80 R13D	165/75 R13D ALUM RIMS
<b>XT-248</b>	4	98	24	29	32	6000	2400	3600	2	2	25	175/80 R13D	165/75 R13D ALUM RIMS
<b>7' WIDE</b>													
<b>PR-127</b>	2	80.5	12	17	20.5	5000	1550	3450	2	2	18	ST205/75 R14C	ST205/75 R14C ALUM RIMS
<b>PR-147</b>	2	80.5	14	19	22.5	5000	1650	3350	2	2	18	ST205/75 R14C	ST205/75 R14C ALUM RIMS
<b>PR-167</b>	2	80.5	16	21	24.5	5000	1750	3250	2	2	18	ST205/75 R14C	ST205/75 R14C ALUM RIMS
<b>PR-187</b>	2-3	80.5	18	23	26.5	6000	1850	4150	2	2	18	ST205/75 R14C	ST205/75 R14C ALUM RIMS
<b>PR-207</b>	2-3	80.5	20	25	28.5	6000	2075	3925	2	2	18	ST205/75 R14C	ST205/75 R14C ALUM RIMS
<b>PR-227</b>	4	80.5	22	27	30.5	6000	2300	3700	2	2	18	ST205/75 R14C	ST205/75 R14C ALUM RIMS
<b>PR-247</b>	4	80.5	24	29	32.5	6000	2525	3475	2	2	18	ST205/75 R14C	ST205/75 R14C ALUM RIMS
<b>8' WIDE</b>													
<b>PR-128-1</b>	2	98	12	17	20	2995	1390	1605	1	2	25	175/80 R13D	165/75 R13D ALUM RIMS
<b>PR-128-2</b>	2	98	12	17	20	5000	1600	3400	2	2	25	175/80 R13D	165/75 R13D ALUM RIMS
<b>PR-168</b>	2-3	98	16	21	24	5000	1900	3100	2	2	25	175/80 R13D	165/75 R13D ALUM RIMS
<b>PR-208</b>	3-4	98	20	25	28	6000	2350	3650	2	2	25	175/80 R13D	165/75 R13D ALUM RIMS
<b>PR-228</b>	4	98	22	27	30	6000	2475	3525	2	2	25	175/80 R13D	165/75 R13D ALUM RIMS
<b>PR-248</b>	4	98	24	29	32	6000	2600	3400	2	2	25	175/80 R13D	165/75 R13D ALUM RIMS
<b>LOW BOY</b>													
<b>PR-LB 16</b>	2-3	98	16	21	24.5	7000	2280	4720	2	2 5/16	16.5	ST205/75 R15C ALUM RIMS	
<b>PR-LB 20</b>	3-4	98	20	25	28.5	7000	2530	4470	2	2 5/16	16.5	ST205/75 R15C ALUM RIMS	
<b>PR-LB 22</b>	4	98	22	27	30.5	7000	2665	4335	2	2 5/16	16.5	ST205/75 R15C ALUM RIMS	
<b>PR-LB 24</b>	4	98	24	29	32.5	7000	2800	4200	2	2 5/16	16.5	ST205/75 R15C ALUM RIMS	
<b>PR-HD 20</b>	3-4	98	20	25	28.5	9995	2800	7195	2	2 5/16	20.5	ST225/75R 15E ALUM RIMS	
<b>PR-HD 22</b>	4	98	22	27	30.5	9995	2900	7095	2	2 5/16	20.5	ST225/75R 15E ALUM RIMS	
<b>PR-HD 24</b>	4	98	24	29	32.5	9995	3000	6995	2	2 5/16	20.5	ST225/75R 15E ALUM RIMS	
<b>PR-HD 28</b>	4	98	28	33	36.5	9995	3300	6695	2	2 5/16	20.5	ST225/75R 15E ALUM RIMS	

\*Hitch Height of ball will increase 4" if equipped with Surge Disc brakes. Measure your particular vehicles for needed model size. Recommended tongue weight for all enclosed trailers is 7-10% of GVWR. Please note: It is the responsibility of the purchaser to adhere to the brake laws regarding trailers. For full information on the laws in your state, contact the appropriate State Motor Vehicle Department. Brake options will change the overall length of trailer. Brake options are surge disc brakes or electric drum brakes. Contact your local dealer for order lead times. All trailers ordered without brakes will have a GVWR of 2995#. Specifications, & accessories can change without notice. US PATENT NUMBERS: 6,247,719 B1 6,186,580 B1 7,147,417 6,439,814 5,823,559 7,077,616 B2