

APT SERIES



**ALL PURPOSE (APT) REAR RAMP
LOADING, NON-TILT TRAILERS
FOR HAULING UTILITY LOADS**



Shown w/optional
spare tire, spare
tire carrier

APT610, 6'X10'
single axle
utility trailer



Shown w/optional spare
tire, spare tire carrier,
aluminum rims, and
aluminum dia. plate
storage box

APT612, 6'X12'
single axle
utility trailer




Shown w/optional spare
tire, spare tire carrier,
aluminum rims, and
aluminum dia. plate
storage box

APT614, 6'X14'
single axle
utility trailer

TRAILERS ARE SHOWN W/OPTIONS

APT ACCESSORIES:

APT's Endgate Kit #15293 slips right into the existing aluminum side kit on the trailers. This provides a sturdy wood wall to contain your loads with a 1" thick fully treated marine grade plywood board for years of use.



Altnoel 5 cu. ft.
of room

Aluminum Diamond Plate Storage Box #05031-1 (LEFT) and the #15331-1 (RIGHT) comes with a keyed lid latch and mounting hardware. Store your straps and other gear separately.



21"W x 10"H x 9"D

**Extra APT
Tiedown Kits
#15292** to secure
even more items
and materials.
(sold in pairs)



Two S-hook
slots punched
in the front
cross member
for tiedown
strap S-hooks



**Spare Tire Carrier
Kit #15430** comes
with the mounting
hardware, and
lockable pin with
optional padlock

SPECIFICATIONS:

MODELS	TRAILER WEIGHT	GVWR WITHOUT BRAKES	CARRYING CAPACITY WITHOUT BRAKES	GVWR WITH BRAKES	CARRYING CAPACITY WITH BRAKES	BED WIDTH	OVERALL WIDTH	OVERALL LENGTH	BED LENGTH	HITCH HEIGHT	DECK HEIGHT	STANDARD TIRES	OPTIONAL TIRES
APT610	650	2995	2345	3500	2850	72	92.0	158	120	17	20	ST205/75D15C	ST205/75R15C ALUM
APT612	705	2995	2290	3500	2795	72	92.0	182	144	17	20	ST205/75D15C	ST205/75R15C ALUM
APT614	780	2995	2215	3500	2720	72	92.0	206	168	17	20	ST205/75D15C	ST205/75R15C ALUM

Please Note: Recommended tongue weight 7-10% of GVWR. All trailers have 2" ball couplers. Prices and specifications may change without notice. It is the responsibility of the purchaser to adhere to the brake laws regarding trailers. For full information on the laws in your state, contact the appropriate State Motor Vehicle Dept. Call your local dealer for lead times.

**ELECTRIC DRUM BRAKES ARE
OPTIONAL ON APT'S**

CALL OR VISIT
US ONLINE: **800-232-3780**

WWW.TRITONTRAILERS.COM



SCAN THIS CODE FOR
THE APT WEBPAGES



Please Note: Recommended tongue weight 7-10% of GVWR. *Brake options will change the overall length of trailer. Brakes are standard on all Car Haulers (both elec. only). AUT1482-2, AUT1682 (one elec. std., 2nd opt.), UT16-7 (one std., 2nd opt., either surge or elec.). All Trailers have 2" ball couplers except for the AUT1482-2, AUT1682, UT16-7 & Car Hauler Series which have a 2 5/16" ball size. Upgraded tires will change deck heights. Prices and specifications may change without notice. It is the responsibility of the purchaser to adhere to the brake laws regarding trailers. For full information on the laws in your state, contact the appropriate State Motor Vehicle Dept.

SPECIFICATIONS:

MODEL	TRAILER WEIGHT	WITHOUT BRAKES		WITH BRAKES		AXLE QTY.	OVERALL WIDTH	BED WIDTH	OVERALL LENGTH	BED LENGTH	HITCH LENGTH	DECK HEIGHT	TILT DECK	LOADING STYLE	RAMP STYLE	PLYWOOD THICKNESS	BRAKE OPTIONS	STANDARD TIRES (R= RADIAL TIRES, D= RIAS PLY TIRES)	OPTIONAL TIRES
		GVWR	CARRYING CAPACITY	GVWR	CARRYING CAPACITY														
ATV88	360	1880	1520	--	--	1	79.75	79	150	104	18	22	NO	SIDEREAR	YES	1/2	N/A	18.5X8C	20.5X10C
ATV128	520	2995	2475	3500	2980	1	79.75	79	202	152	22	25.5	NO	SIDEREAR	YES	1/2	SURGE/ELEC	20.5X10E	ST145/R12E
ATV128-2	680	2995	2315	4400	3720	2	79.75	79	202	152	22	25.5	NO	SIDEREAR	YES	1/2	SURGE/ELEC	20.5X10C	ST145/R12E
ATV168	780	2995	2215	4400	3620	2	79.75	79	250	200	22	25.5	NO	SIDEREAR	YES	1/2	SURGE/ELEC	20.5X10C	ST145/R12E
SL8	400	1880	1480	--	--	1	79.75	79	149	101	18	22	NO	SIDE	YES	1/2	N/A	18.5X8C	20.5X10C
SL12	670	2995	2325	3500	2830	1	79.75	79	201	152	22	25.5	NO	SIDE	YES	1/2	SURGE/ELEC	20.5X10E	ST145/R12E
SL12-2	830	2995	2165	4400	3570	2	79.75	79	201	152	22	25.5	NO	SIDE	YES	1/2	SURGE/ELEC	20.5X10C	ST145/R12E
SL16	940	2995	2055	4400	3460	2	79.75	79	249	200	22	25.5	NO	SIDE	YES	1/2	SURGE/ELEC	20.5X10C	ST145/R12E
UT8	440	2700	2260	--	--	1	94	74	142	96	19	22	YES	REAR	OPT.	5/8	N/A	ST175/80D13C	ST175/80D13C ALUM
UT10	520	2700	2180	--	--	1	94	74	166	120	19	22	YES	REAR	OPT.	5/8	N/A	ST175/80D13C	ST175/80D13C ALUM
UT12	780	2995	2215	3500	2720	1	102	81	192	144	21	24	NO	REAR	OPT.	5/8	SURGE/ELEC	ST205/75R14C	ST205/75R14C ALUM
UT12-2	900	2995	2095	6000	5100	2	102	81	192	144	21	24	NO	REAR	OPT.	5/8	SURGE/ELEC	ST205/75D14C	ST205/75R14C ALUM
UT16	1000	2995	1995	6000	5000	2	102	81	238	192	21	24	NO	REAR	OPT.	5/8	SURGE/ELEC	ST205/75D14C	ST205/75R14C ALUM
UT16-7	1175	--	--	7000	5825	2	102	81	238	192	21	24	NO	REAR	OPT.	1	1 AXLE STD. SURGE/ELEC	ST205/75D14C	ST205/75R14C ALUM
GU8	290	1880	1590	--	--	1	72	53	138	96	16	17	YES	REAR	OPT.	1/2	N/A	18.5X8C	4.80X12C
GU10	370	2090	1720	--	--	1	82	64	164	120	17	18	YES	REAR	OPT.	1/2	N/A	5.30X12C	20.5X10C
AUT853 AUT853B	350	2200	1850	--	--	1	75	53	142	96	18	20	NO	REAR	YES	ALUM	N/A	ST175/80D13C	ST175/80D13C ALUM ST205/75D14C ST205/75R14C ALUM
AUT864 AUT864B	375	2200	1825	--	--	1	86	64	142	96	18	20	NO	REAR	YES	ALUM	N/A	ST175/80D13C	ST175/80D13C ALUM ST205/75D14C ST205/75R14C ALUM
AUT1064 AUT1064B	400	2200	1800	--	--	1	86	64	165	120	18	20	NO	REAR	YES	ALUM	N/A	ST175/80D13C	ST175/80D13C ALUM ST205/75D14C ST205/75R14C ALUM
AUT1464	760	2995	2235	3000	2240	1	86	64	226	168	14.5	18.5	NO	REAR	YES	ALUM	SURGE/ELEC	ST205/75R14C	ST205/75R14C ALUM
AUT1464-2	940	2995	2055	4400	3460	2	86	64	226	168	14.5	18.5	NO	REAR	YES	ALUM	SURGE/ELEC	ST205/75D14C	ST205/75R14C ALUM
AUT1082 AUT1082B	680	2995	2315	3500	2820	1	102	82	174	120	14.5	18.5	NO	REAR	YES	ALUM	SURGE/ELEC	ST205/75D14C	ST205/75R14C ALUM
AUT1282 AUT1282B	760	2995	2235	3500	2740	1	102	82	198	144	14.5	18.5	NO	REAR	YES	ALUM	SURGE/ELEC	ST205/75D14C	ST205/75R14C ALUM
AUT1282-2 AUT1282-2B	880	2995	2115	5000	4120	2	102	82	198	144	14.5	18.5	NO	REAR	YES	ALUM	SURGE/ELEC	ST205/75D14C	ST205/75R14C ALUM
AUT1482	860	2995	2135	3500	2640	1	102	82	226	168	14.5	18.5	NO	REAR	YES	ALUM	SURGE/ELEC	ST205/75D14C	ST205/75R14C ALUM
AUT1482-2	1120	--	--	7000	5880	2	102	82	220	168	14.5	18.5	NO	REAR	YES	ALUM	STD. 1-ELEC	ST205/75D14C	ST205/75R14C ALUM
AUT1682	1240	--	--	7000	5760	2	102	82	257	192	14.5	18.5	NO	REAR	YES	ALUM	STD. 1-ELEC	ST205/75D14C	ST205/75R14C ALUM
CH18	1480	--	--	7500	6020	2	102	101	267	216	18	23	NO	SIDEREAR	YES	ALUM	STD. 2-ELEC	ST205/75R15C	ST205/75R15C ALUM
CH20	1600	--	--	7500	5900	2	102	101	291	240	18	23	NO	SIDEREAR	YES	ALUM	STD. 2-ELEC	ST205/75R15C	ST205/75R15C ALUM
CH22	1720	--	--	7500	5780	2	102	101	315	264	18	23	NO	SIDEREAR	YES	ALUM	STD. 2-ELEC	ST205/75R15C	ST205/75R15C ALUM
CHHD18	1810	--	--	9995	8185	2	102	101	284	216	18	23	NO	REAR	YES	ALUM	STD. 2-ELEC	ST225/75R15E	ST225/75R15E ALUM
CHHD20	2010	--	--	9995	7985	2	102	101	308	240	18	23	NO	REAR	YES	ALUM	STD. 2-ELEC	ST225/75R15E	ST225/75R15E ALUM
CHHD22	2210	--	--	9995	7785	2	102	101	332	264	18	23	NO	REAR	YES	ALUM	STD. 2-ELEC	ST225/75R15E	ST225/75R15E ALUM



WE COMPLY WITH
NATM'S STRICT
GUIDELINES FOR
A TRAILER
MANUFACTURER!

Triton U.S. Patent Numbers: 6,439,814
7,147,417 7,077,616 B2 5,823,559
6,247,719 B1 6,186,580 B1 6,616,388

800-232-3780
WWW.TRITONTRAILERS.COM



857 West State Street
Hartford, CT 03027
262-670-6514 fax 262-670-6545