

TRITON Customer Instruction Sheet

KIT NO.:
11994

DESCRIPTION

ROOF RACK

DRAWN BY:
Terri Feutz
DATE:
2-28-06

DRAWING NO.:
12002

Parts List

ITEM	PART N	DESCRIPTION	QTY
1	11988	BRACKET, ROOF RACK STOP	2
2	11986	TUBE, ADJUSTABLE ROOF RACK	1
3	11995	BRACKET, MOUNTING ROOF RACK	2
4	12001	WASHER, BOND SEAL 3/8 Z/Y	8
5	07470	BOLT, HHCS 3/8-16 x 1 1/4 SS	4
6	05515	NUT, HEX 3/8-16 LOC SS	4
7	06181	WASHER, FLAT 1/4 SS	16
8	06206	BOLT, HHCS 1/4-20 X 1 SS	8
9	05513	NUT, HEX 1/4-20 LOC SS	8
10	11993	PLUG, 1 1/2 X 2 1/2 BLACK	2

IF NEEDED SAW 11986 - TUBE TO CORRECT LENGTH
(SEE BELOW).

SLIDE 11988 - BRACKET, ROOF RACK STOP ONTO 11986 -
TUBE POSITIONED AS SHOWN. BE SURE THE DRAIN
HOLE IN TUBE IS TO THE BOTTOM SIDE. ATTACH 11995 -
BRACKET, MOUNTING WITH HARDWARE AS SHOWN (SEE
DETAIL B). INSTALL 08287 - PLUG IN ENDS OF TUBE.

LOCATE ROOF RACK ASSEMBLY ON ROOF OF TRAILER.
REST EDGE OF ROOF RACK BRACKET ON 'GUTTER' OF
ROOF COVE. USING THE ROOF RACK BRACKET AS A
TEMPLATE, DRILL THROUGH ROOF COVE BEING
CAREFULL NOT TO DAMAGE THE WIRING SYSTEM WHICH
IS FOUND INSIDE OF THE COVE. MOUNT WITH
HARDWARE AS SHOWN.

DETAIL B

